

I.2 Vertical water heater on base (VB)

		150 l	200 litres		250 litres		300 litres	
Voltage (V)		230 V single-phase						
Resistance		Shielded	Shielded	Steatite	Shielded	Steatite	Shielded	Steatite
Power (W)		1,650	2,200	2,200	3,000	3,000	3,000	3,000
Dimensions (mm)	Ø	530	530	530	530	530	570	570
	H	1,170	1,485	1,485	1,805	1,805	1,765	1,765
	A	300	300	300	300	300	300	300
	B	600	600	600	600	600	640	640
Real heating time**		4 h 46 min	4 h 41 min	4h 57 min	4 h 40 min	4 h 55 min	5 h 53 min	5 h 37 min
Qpr (Maintenance consumption)***		1.53	1.45	1.88	2.15	2.22	2.58	2.49
V40 (Amount of hot water at 40°C)		259	358	354	477	465	569	531
Weight when empty (kg)		37	43	43	57	58	65	68
Weight when full (kg)		187	243	243	307	308	365	368

		200 l	250 l	300 l
Voltage (V)		All currents*		
Resistance		Shielded	Shielded	Shielded
Power (W)		2,200	3,000	3,000
Dimensions (mm)	Ø	530	530	570
	H	1,485	1,805	1,765
	A	300	300	300
	B	600	600	640
Real heating time**		4 h 41 min	4 h 40 min	5 h 53 min
Qpr (Maintenance consumption)***		1.45	2.15	2.58
V40 (Amount of hot water at 40°C)		358	477	569
Weight when empty (kg)		44	57	68
Weight when full (kg)		244	307	368

*Appliances supplied with three-phase wiring 230/400V3~ can be switched to 230 V single-phase~

**Real heating time for heating from 15° to 65°C

***Maintenance consumption in kWh for 24 hours for water at 65°C (ambiance 20°C)

Diagrammatic representation

