

FLEXIBLE SOLUTIONS, INFINITE COMBINATIONS!

WWW.FIXAFLEX.COM

FIXAFLEX N.V.
POLDERHOEK
KASTEELSTRAAT 15
8980 GELUVELD
BELGIUM

PRODUCT

ARTICLE: 25.10.0750.C
DESCRIPTION: EPDM-ACS DN32 INOX 5/4"M - 5/4"F INOX-CSTB L750

PARTS

BRAIDED HOSES

DN: 32
Material of hose: EPDM-ACS
Braiding: INOX 10x0,25mm AISI304L
Pressure: 8 BAR
Temperature: - 30°C / +110°C
Diameter: 32 x 42 mm

SLEEVE

Dimensions: 45,5 x 47 mm
Material: INOX -CSTB

CERTIFICATIONS

☒	CSTB	☐	SVGW
☐	KIWA	☐	DVGW
☒	ACS		

FITTING LEFT

Dimension type: 5/4"F for DN32
Integrated seal: No
Thread: ISO228/1
Finishing fitting: Brass brut
Finishing nut: Brass nickel-plated
Bore diameter: 25,5 mm

FITTING RIGHT

Dimension type: 5/4"M for DN32
Integrated seal: No
Thread: ISO228/1
Finishing fitting: Brass brut
Finishing nut: -
Bore diameter: 25,5 mm



750mm -0mm / +20mm

*Please note that the drawing is not on realistic scale



FIXAFLEX
YOUR FLEXIBLE HOSE REFERENCE