


SANCO-Rohr in Stangen

- Festigkeit: **hart R290** und **halbhart R250**
- in Längen von 5 m



	Artikelnummer	Lieferform Stangen	zulässiger Betriebsdruck* bar	Gewicht kg/m	Wasserinhalt l/m	Rohrlänge pro Liter m/l
6 x 1	431800100	•	229	0,140	0,013	79,58
8 x 1	431800200	•	163	0,196	0,028	35,37
10 x 1	433410100	•	127	0,252	0,050	19,89
12 x 1	433612100	hh	104	0,308	0,079	12,73
15 x 1	433615100	hh	82	0,391	0,133	7,53
18 x 1	433618100	hh	67	0,475	0,201	4,97
22 x 1	433622100	hh	54	0,587	0,314	3,18
28 x 1	433628100	hh	42	0,755	0,531	1,88
28 x 1,5	433628150	hh	65	1,110	0,491	2,04
35 x 1,2	433435120	•	41	1,134	0,835	1,20
35 x 1,5	431801500	•	51	1,410	0,804	1,24
42 x 1,2	433442120	•	34	1,369	1,232	0,81
42 x 1,5	431801700	•	42	1,700	1,195	0,84
54 x 1,5	433454150	•	33	2,202	2,043	0,49
54 x 2	431802000	•	44	2,910	1,963	0,51