



# resideo

## Centra Linear Valve VDE/VXE/VYE

### Small Linear Valves

#### APPLICATION

These small linear valves are used in combination with small electric linear valve actuators and thermoelectric actuators for the control of hot and/or chilled water for fan coil units and small reheaters/recoolers in electric/electronic temperature control systems.

#### SPECIAL FEATURES

- Dezincification-resistant yellow brass
- No maintenance work is required
- Wide standardized range of  $k_{VS}$  values
- Reduced  $k_{VS}$  values in the bypass to facilitate hydronic balancing (VYE version)
- Range of fittings available for different connections (compression, soldered, threaded)
- Small size allows installation where space is limited
- Long stroke results in a high-quality characteristic
- Soft seat for low leakage rate and high rangeability
- High close-off pressure


#### TECHNICAL DATA

Media	
Medium:	Water with max. 50 % glycol according to VDI 2035
Water temperature:	2...120 °C
Connection/Sizes	
Valve size:	DN15 (G <sup>1/2</sup> *), DN20 (G <sup>3/4</sup> *), DN25 (G1 <sup>1/4</sup> *)
Specifications	
Model:	2-way valve: VDE 3-way valve: VXE 3-way valve with bypass: VYE
Operation:	All models stem up to close, port A to B / AB
Nominal pressure rating:	PN 16
Capacity index ( $k_{VS}$ ):	See chapter „Flow capacities and close-off pressure ratings“
Close-off pressures:	
Leakage rate:	≤0.02 % of $k_{VS}$
Port connection:	Conical and flat sealing connections in standard sizes



Modulating valves	
Stroke:	6.5 mm
Closure distance:	18 mm
Flow characteristic:	2-way valve: - modified equal % 3-way valve: - modified equal % for port A-AB - Linear for port B-AB
ON/OFF valves	
Stroke:	2.5 mm
Closure distance:	14 mm
Snap-on valves	
Stroke:	2.5 mm
Closure distance:	5 mm

## CONSTRUCTION

Overview	Components	Materials
	1 Valve body	Brass resistant to dezincification
	<b>Not depicted components:</b>	
	Stem	Stainless steel
	Plug	Brass, EPDM seals

## METHOD OF OPERATION

All types of valves should be mounted in the return flow. If the  $\Delta p$ -values exceed 300 kPa, attention should be paid to the development of noise.

In the case of the 2-way valve, the 3-way valve and the 3-way valve with bypass, the built-in spring produces a closing force on the A-B / A-AB ports.


The valves are supplied with a screwed-on adjustment cap for manual operation and for protection of the stem. If it should become necessary to flush the system, the valve can be opened between approx. 50% and 75% of the rated kVS with the protection cap attached or fully opened via a connected actuator.

This allows the stem to be set up for filling or initial heating/cooling during the building construction phase without the use of a controller or actuator.

The small electric valve actuators as well as the thermoelectric actuators provide automatic control over the opening and closing movement of the valve stem.

### 2-way valves

Direction of flow always from port A to port B  
Port B: Outlet




### 3-way valves

These valves are preferably used as mixing valves, this means:

Port A: Controlled flow inlet


Port B: Outlet

Port AB: Total flow outlet



### 3-way valves with Bypass

These valves simplify the installation, which is depending on the layout of the pipework, as the bypass pipe is part of the valve. The information for the normal 3-way valves is also valid for this type.



## INSTALLATION GUIDELINES

### Mounting

When installing the valve care must be taken that the flow direction is correct (see section). The valve must not be mounted with the stem pointing downward.

The adjustment cap must be removed from the valve only when the actuator is fitted. The valve should be installed as stress-free as possible with a tightening torque of 25 to 30 Nm.

The valve is supplied complete with mounting instructions.


Note: Mount the actuator by hand, only. Do not use a tool, as this could result in damage.

### Disposal

Statutory regulations and/or environmental protection considerations may require special handling in disposing of the valves


# TECHNICAL CHARACTERISTICS

## Valve action with MT4/MT8-Series Smart-T Thermal Actuators




## DIMENSIONS

### VDE... (2-way)




Type	DN	A	B	C	Stroke		Closure distance	
					e	F		
Conical sealing	15	56	G 1/2" A*	32	Modulating: 6.5 mm On/Off: 2.5 mm	Modulating: 18 mm On/Off: 14 mm		
	20	66	1 1/8 14 BS84	34				
	25	76	G 1 1/4" A*	48				
Flat sealing	15	56	G 1/2" A*	32				
	20	66	G 3/4" A*	34				
	25	76	G 1 1/4" A*	48				

### VDE...SN (2-way with snap-on)




Type	DN	A	B	C	Stroke		Closure distance	
					e	F		
Flat sealing	20	66	G 3/4" A*	36.6	Modulating: 2.5 mm	Modulating: 5 mm		

### VXE... (3-way)



Type	DN	A	B	C	D	Stroke		Closure distance	
						e	F		
Conical sealing	15	56	G 1/2" A*	24.5	32	Modulating: 6.5 mm On/Off: 2.5 mm	Modulating: 18 mm On/Off: 14 mm		
	20	66	1 1/8 14 BS84	33	34				
	25	76	G 1 1/4" A*	38	48				
Flat sealing	15	56	G 1/2" A*	25.5	32				
	20	66	G 3/4" A*	33	34				
	25	76	G 1 1/4" A*	38	48				

**VYE... (3-way with bypass)****Overview**

Type	DN	A	B	C	D	Stroke	Closure distance
						e	F
Conical sealing	15	56	G 1/2" A*	40	32	Modulating: 6.5 mm On/Off: 2.5 mm	Modulating: 18 mm On/Off: 14 mm
	20	66	1 1/8 14 BS84	40	34		
	25	76	G 1 1/4" A*	62.5	48		
Flat sealing	15	56	G 1/2" A*	40	32		
	20	66	G 3/4" A*	40	34		
	25	76	G 1 1/4" A*	62.5	48		

\*ISO 228/1

Note: All dimensions in mm unless stated otherwise.

**ORDERING INFORMATION**

The following tables contain all the information you need to make an order of an item of your choice.

When ordering, please always state the type, the ordering or the part number.

**Naming key linear valves**

VD	E	15	B	1.6	OF
Type of valve	Type of thread	DN (mm)	PN (bar)	k <sub>VS</sub> -value	Special (optional)
VD = 2-way small linear valve	E = External	15	B = 16	0.16	OF = On/Off M = Modulating P = Pressure balanced C/CS = Conical Sealing SN = Snap-On
VX = 3-way small linear valve		20		0.25	
VY = 3-way small linear valve with bypass		25		0.4	
		0.63			
		1.0			
		1.6			
		2.5			
		4.0			
		5.5			
		6.3			
		8.0			

**Flow capacities and close off pressure ratings****VDE Valves (2-way valves)**

DN	K <sub>vs</sub> A-B	Type	Stroke	Close-off pressure	Pressure balanced	OS-No.
<b>2-way valves modulating with flat sealing</b>						
15	0.16	MOD	6.5	600 kPa		VDE15B0.16M
15	0.25	MOD	6.5	600 kPa		VDE15B0.25M
15	0.40	MOD	6.5	600 kPa		VDE15B0.4M
15	0.63	MOD	6.5	600 kPa		VDE15B0.63M
15	1.0	MOD	6.5	600 kPa		VDE15B1.0M
15	1.6	MOD	6.5	300 kPa		VDE15B1.6M
15	2.5	MOD	6.5	100 kPa		VDE15B2.5M
20	2.5	MOD	6.5	150 kPa		VDE20B2.5M
20	4.0	MOD	6.5	50 kPa		VDE20B4.0M
25	6.3	MOD	6.5	250 kPa	•	VDE25B6.3MP
25	8.0	MOD	6.5	250 kPa	•	VDE25B8.0MP
<b>2-way valves on-off with flat sealing</b>						
15	1.0	ON-OFF	2.5	600 kPa		VDE15B1.0OF
15	1.6	ON-OFF	2.5	300 kPa		VDE15B1.6OF
15	2.5	ON-OFF	2.5	150 kPa		VDE15B2.5OF
20	2.5	ON-OFF	2.5	200 kPa		VDE20B2.5OF
20	2.5	ON-OFF, Snap on*	2.5	200 kPa		VDE20B2.5OFSN
20	4.0	ON-OFF	2.5	100 kPa		VDE20B4.0OF
25	4.0	ON-OFF	2.5	200 kPa	•	VDE25B4.0OFP
20	4.0	ON-OFF, Snap on*	2.5	200 kPa		VDE20B4.0OFSN
25	5.5	ON-OFF	2.5	200 kPa	•	VDE25B5.5OFP
<b>2-way valves modulating with conical sealing</b>						
15	0.16	MOD	6.5	600 kPa		VDE15B0.16MCS
15	0.25	MOD	6.5	600 kPa		VDE15B0.25MCS
15	0.40	MOD	6.5	600 kPa		VDE15B0.4MCS
15	0.63	MOD	6.5	600 kPa		VDE15B0.63MCS
15	1.0	MOD	6.5	600 kPa		VDE15B1.0MCS
15	1.6	MOD	6.5	300 kPa		VDE15B1.6MCS
15	2.5	MOD	6.5	100 kPa		VDE15B2.5MCS
20	2.5	MOD	6.5	150 kPa		VDE20B2.5MCS
20	4.0	MOD	6.5	50 kPa		VDE20B4.0MCS
25	6.3	MOD	6.5	250 kPa	•	VDE25B6.3MPC
25	8.0	MOD	6.5	250 kPa	•	VDE25B8.0MPC
<b>2-way valves on-off with conical sealing</b>						
15	1.6	ON-OFF	2.5	300 kPa		VDE15B1.6OFCS
20	2.5	ON-OFF	2.5	200 kPa		VDE20B2.5OFCS

\* To be used directly with MT4/MT8 thermoelectric actuator without adapter because of integrated Snap-On connection

**VXE Valves (3-way valves)**

DN	K <sub>vs</sub>		Type	Application	Stroke	Close-off pressure	Pressure balanced	OS-No.
	A-AB	B-AB						
<b>3-way valves modulating with flat sealing</b>								
15	0.25	0.16	MOD	MIX	6.5	600 kPa		VXE15B0.25M
15	0.40	0.25	MOD	MIX	6.5	600 kPa		VXE15B0.4M
15	0.63	0.40	MOD	MIX	6.5	600 kPa		VXE15B0.63M
15	1.0	0.63	MOD	MIX	6.5	600 kPa		VXE15B1.0M
15	1.6	1.0	MOD	MIX	6.5	300 kPa		VXE15B1.6M
15	2.5	1.6	MOD	MIX	6.5	100 kPa		VXE15B2.5M
20	2.5	1.6	MOD	MIX	6.5	150 kPa		VXE20B2.5M
20	4.0	2.5	MOD	MIX	6.5	50 kPa		VXE20B4.0M
25	6.3	4.0	MOD	MIX	6.5	250 kPa	•	VXE25B6.3MP
25	8.0	5.5	MOD	MIX	6.5	250 kPa	•	VXE25B8.0MP
<b>3-way valves on-off with flat sealing</b>								
15	1.0	0.63	ON-OFF	MIX/DIV	2.5	600/200 kPa		VXE15B1.0OF
15	1.6	1.0	ON-OFF	MIX/DIV	2.5	300/200 kPa		VXE15B1.6OF
15	2.5	1.6	ON-OFF	MIX	2.5	150 kPa		VXE15B2.5OF
20	2.5	1.6	ON-OFF	MIX	2.5	200 kPa		VXE20B2.5OF
20	4.0	2.5	ON-OFF	MIX	2.5	100 kPa		VXE20B4.0OF
25	4.0	2.5	ON-OFF	MIX	2.5	200 kPa	•	VXE25B4.0OFP
25	5.5	3.5	ON-OFF	MIX	2.5	200 kPa	•	VXE25B5.5OFP
<b>3-way valves modulating with conical sealing</b>								
15	0.25	0.16	MOD	MIX	6.5	600 kPa		VXE15B0.25MCS
15	0.40	0.25	MOD	MIX	6.5	600 kPa		VXE15B0.4MCS
15	0.63	0.40	MOD	MIX	6.5	600 kPa		VXE15B0.63MCS
15	1.0	0.63	MOD	MIX	6.5	600 kPa		VXE15B1.0MCS
15	1.6	1.0	MOD	MIX	6.5	300 kPa		VXE15B1.6MCS
15	2.5	1.6	MOD	MIX	6.5	100 kPa		VXE15B2.5MCS
20	2.5	1.6	MOD	MIX	6.5	150 kPa		VXE20B2.5MCS
20	4.0	2.5	MOD	MIX	6.5	50 kPa		VXE20B4.0MCS
25	6.3	4.0	MOD	MIX	6.5	250 kPa	•	VXE25B6.3MPC
25	8.0	5.5	MOD	MIX	6.5	250 kPa	•	VXE25B8.0MPC
<b>3-way valves on-off with conical sealing</b>								
15	1.6	1.0	ON-OFF	MIX/DIV	2.5	300/200 kPa		VXE15B1.6OFCS
20	2.5	1.6	ON-OFF	MIX	2.5	200 kPa		VXE20B2.5OFCS

**VYE Valves (3-way valves with bypass)**

DN	K <sub>vs</sub>		Type	Application	Stroke	Close-off pressure	Pressure balanced	OS-No.
	A-AB	B-AB						
<b>3-way valves with bypass modulating with flat sealing</b>								
15	0.25	0.16	MOD	MIX	6.5	600 kPa		VYE15B0.25M
15	0.40	0.25	MOD	MIX	6.5	600 kPa		VYE15B0.4M
15	0.63	0.40	MOD	MIX	6.5	600 kPa		VYE15B0.63M
15	1.0	0.63	MOD	MIX	6.5	600 kPa		VYE15B1.0M
15	1.6	1.0	MOD	MIX	6.5	300 kPa		VYE15B1.6M
15	2.5	1.6	MOD	MIX	6.5	100 kPa		VYE15B2.5M
20	2.5	1.6	MOD	MIX	6.5	150 kPa		VYE20B2.5M
20	4.0	2.5	MOD	MIX	6.5	50 kPa		VYE20B4.0M
25	6.3	4.0	MOD	MIX	6.5	250 kPa	•	VYE25B6.3MP
25	8.0	5.5	MOD	MIX	6.5	250 kPa	•	VYE25B8.0MP
<b>3-way valves with bypass on-off with flat sealing</b>								
15	1.0	0.63	ON-OFF	MIX/DIV	2.5	600/200 kPa		VYE15B1.0OF
15	1.6	1.0	ON-OFF	MIX/DIV	2.5	300/200 kPa		VYE15B1.6OF
15	2.5	1.6	ON-OFF	MIX	2.5	150 kPa		VYE15B2.5OF
20	2.5	1.6	ON-OFF	MIX	2.5	200 kPa		VYE20B2.5OF
20	4.0	2.5	ON-OFF	MIX	2.5	100 kPa		VYE20B4.0OF
25	4.0	2.5	ON-OFF	MIX	2.5	200 kPa	•	VYE25B4.0OFP
<b>3-way valves with bypass modulating with conical sealing</b>								
15	0.25	0.16	MOD	MIX	6.5	600 kPa		VYE15B0.25MCS
15	0.40	0.25	MOD	MIX	6.5	600 kPa		VYE15B0.4MCS
15	0.63	0.40	MOD	MIX	6.5	600 kPa		VYE15B0.63MCS
15	1.0	0.63	MOD	MIX	6.5	600 kPa		VYE15B1.0MCS
15	1.6	1.0	MOD	MIX	6.5	300 kPa		VYE15B1.6MCS
15	2.5	1.6	MOD	MIX	6.5	100 kPa		VYE15B2.5MCS
20	2.5	1.6	MOD	MIX	6.5	150 kPa		VYE20B2.5MCS
20	4.0	2.5	MOD	MIX	6.5	50 kPa		VYE20B4.0MCS
25	6.3	4.0	MOD	MIX	6.5	250 kPa	•	VYE25B6.3MPC
25	8.0	5.5	MOD	MIX	6.5	250 kPa	•	VYE25B8.0MPC
<b>3-way valves with bypass on-off with conical sealing</b>								
15	1.6	1.0	ON-OFF	MIX	2.5	300/200 kPa		VYE15B1.6OFCS
20	2.5	1.6	ON-OFF	MIX	2.5	200 kPa		VYE20B2.5OFCS

## Accessories




## Overview associated actuators

Valve stroke	Control signal				
	On/Off 230 V	On/Off 24 V	3-point 230 V	3-point 24 V	0/2...10 V 24 V
2.5 mm	MT4-230...NC/NO	MT4-024...NC/NO			
6.5 mm	MT8-230...NC/NO M5410L1001	MT8-024...NC/NO M5410C1001	M6410L2023 M6410L4029	M6410C2023 M6410C4029 M7410C1007	M7410E1002 M7410E2026 M7410E4022

	Description	Power Supply	Part No.
	<b>MT4</b> <b>Actuator: 4.0 mm stroke, 90 N, on/off, thermoelectric</b>		
	NO = Normally open	24 V AC/DC	MT4-024-NO
	NC = Normally closed	24 V AC/DC	MT4-024-NC
	NO = Normally open	230 V AC	MT4-230-NO
	NC = Normally closed	230 V AC	MT4-230-NC
	<b>MT8</b> <b>Actuator: 8.0 mm stroke, 90 N, on/off, thermoelectric</b>		
	NO = Normally open	24 V AC/DC	MT8-024-NO
	NC = Normally closed	24 V AC/DC	MT8-024-NC
	NO = Normally open	230 V AC	MT8-230-NO
	NC = Normally closed	230 V AC	MT8-230-NC
	<b>M5410</b> <b>Actuator: 6.5 mm stroke, 100 N, on/off, fast motorized</b>		
	Note: Closes when power fails		
		24 V AC	M5410C1001
	230 V	M5410L1001	
	<b>M6410</b> <b>Actuator: 6.5 mm stroke, 180 N, 3-point, floating</b>		
	Manual override	24 V AC	M6410C2023
	Manual override, 2 auxiliary switches	24 V AC	M6410C4029
	Manual override	230 V AC	M6410L2023
	Manual override, 2 auxiliary switches	230 V AC	M6410L4029
	<b>M7410C</b> <b>Actuator: 6.5 mm stroke, 180 N, 3-point / floating</b>		
		24 V AC	M7410C1007
	<b>M7410E</b> <b>Actuator: 6.5 mm stroke, 300 N, 0/2 - 10 V, modulating</b>		
		24 V AC	M7410E1028
	Manual override	24 V AC	M7410E2034
	Manual override, 2 auxiliary switches	24 V AC	M7410E4030

**Naming key linear valves accessories**

ASV	-CS	-20	-O	-F
Accessories for V&A	Connection set	DN (mm)	Fitting type	Sealing type
ASV = Accessories for V&A	CS = Connection set	15 20 25	F = CONEX Fitting S = Soldered O = Outer thread	F = Flat C = Conical

	<b>ASV-CS-xx-F-C Conical connection set</b>	Consisting of one union nut and one ferrule, compression connection		
		$b = G^{1/2}$ , $e = 15 \text{ mm}$	DN15	ASV-CS-15-F-C
		$b = 1^{1/8} \times 14 \text{ BS } 84$ , $e = 22 \text{ mm}$	DN20	ASV-CS-20-F-C
	<b>ASV-CS-xx-O-C Conical connection set</b>	Consisting of one union nut and one tailpiece, external thread		
		$b = G^{1/2}$ , $g = R^{3/8}$ "	DN15	ASV-CS-15-O-C
		$b = 1^{1/8} \times 14 \text{ BS } 84$ , $g = R^{1/2}$ "	DN20	ASV-CS-20-O-C
	<b>ASV-CS-xx-S-F Flat connection set</b>	Consisting of one union nut, one solder bush and one gasket, soldering connection		
		$b = G^{1/2}$ , $f = 12 \text{ mm}$	DN15	ASV-CS-15-S-F
		$b = G^{3/4}$ , $f = 15 \text{ mm}$	DN20	ASV-CS-20-S-F
	<b>ASV-CS-xx-O-F Flat connection set</b>	Consisting of one union nut, one tailpiece with external thread and one gasket		
		$b = G^{1/2}$ , $g = R^{3/8}$ "	DN15	ASV-CS-15-O-F
		$b = G^{3/4}$ , $g = R^{1/2}$ "	DN20	ASV-CS-20-O-F
		$b = G^{1^{1/4}}$ , $g = R1$ "	DN25	ASV-CS-25-O-F2

Note: VDE needs two connection sets, VXE needs three connection sets, VYE needs four connection sets



Manufactured for  
and on behalf of  
Pittway Sàrl, Z.A., La Pièce 4  
1180 Rolle, Switzerland

For more information  
[homecomfort.resideo.com/europe](http://homecomfort.resideo.com/europe)  
Ademco 1 GmbH, Hardhofweg 40,  
74821 MOSBACH, GERMANY  
Phone: +49 6261 810  
Fax: +49 6261 81309

This document contains proprietary information of Pittway Sàrl and its affiliated companies and is protected by copyright and other international laws. Reproduction or improper use without specific written authorization of Pittway Sàrl is strictly forbidden.