Reflex Exdirt D 100, dirt separator with flange, 110 °C, 10 bar

Article number: 8252330

reflex



Features

| Туре | D 100 |
|----------------------------------------|---------------|
| Colour | grey |
| Housing material | painted steel |
| Installation variant | horizontal |
| Operating temperature | 0 °C - 110 °C |
| Operating pressure | 10 bar |
| Connection | DN100/PN16 |
| Cleaning connection | IG 1" |
| Connection variant | flange |
| Max. volume flow | 47,0 m³/h |
| Flow rate characteristic value kvs | 244,3 m³/h |
| Diameter | 206 mm |
| Height | 636 mm |
| Height mid-flange (dirt separation) | 180 mm |
| Min. maintenance height | 370 mm |
| Installation length | 470 mm |
| Weight | 19,00 kg |

Description

Reflex Exdirt

Dirt and sludge separator for heating and cooling water systems or closed liquid-filled plant systems. Suitable for the media water and water/glycol mixtures up to a mixing ratio of 50/50%. Fitting for removing particles with a size of up to 5.0

micrometres from the flow of liquid by use of an insert designed specially for the purpose.

The cleaning and emptying of the dirt collection chamber is possible via a dedicated desludging ball valve without any necessity to interrupt operation.

