



## DECLARATION OF PERFORMANCE

*In compliance with EU Regulation (EU): No 305/2011 of March 9/2011  
(Construction Product Regulation - CPR)*

Declaration of Performance-Nr. **GR 00208**

1. Unique identification code of the product-type:

**Sealants for facade elements**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Acrylic Sealant A-100 White**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealants for facade elements for interior and exterior applications  
Applicable norm: EN 15651-1: 2012; F-EXT-INT (7,5P)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**BISON INTERNATIONAL, Dr. A.F. Philipsstraat 9, NL - 4462 EW Goes, Netherlands**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not Applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

**System 3 for reaction to fire according class E**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
**The product type has been tested by the registered inspection agency SKZ – TeConA GmbH (1213) according to EN 15651-1: 2012 and reaction to fire according system 3 and provided a test report.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not Applicable**

9. Declared performance

Conditioning: Procedure A (according to ISO 8339)

Substrate: Mortar M2 (without use of primor)

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1 :2012
Release of chemicals dangerous to the environment and health	NPD	
<b>Water tightness and Air tightness</b>		
Resistance to flow	≤3 mm	
Loss of Volume	≤ 10%	
Tensile properties (i.e. elongation): at maintained extension after water immersion	Pass	
Tensile properties (i.e. elongation) at break at (23 °C)	≥ 25%	

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **Not Applicable**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of Bison International.

Signed on behalf of Bison International by:

Name : S.C.J.A. Christiaansen  
 Function : General Manager PSO / Director Professional Business  
 Place and date : Goes, 30 juni 2014  
 Signature :

