


Geberit PE Abzweig 88,5°



Verwendungszwecke

- Zur Gebäudeentwässerung

Technische Daten

Werkstoff

PE-HD

Artikel

Art.-Nr.	DN	d, ø [mm]	d1, ø [mm]	H [cm]	X1 [cm]	X2 [cm]	X3 [cm]	K1 [cm]	K2 [cm]	K3 [cm]	VE4 [St.]	VE3 [St.]	VE2 [St.]	VE1 [St.]
379.158.16.1	30 / 30	32	32	8,5	5	3,5	3,5	2,5	1	1			10	1
360.158.16.1	40 / 30	40	32	13	7,5	5,5	5,5	5	2,5	2			10	1
360.159.16.1	40 / 40	40	40	13	7,5	5,5	5,5	4,5	2,5	2,5		50	10	1
361.159.16.1	50 / 40	50	40	15	9	6	6	6	2,5	3			10	1
361.162.16.1	50 / 50	50	50	15	9	6	6	5,5	2,5	2,5	800	50	10	1
363.162.16.1	56 / 50	56	50	17,5	10,5	7	7	7	3	3,5			10	1
363.165.16.1	56 / 56	56	56	17,5	10,5	7	7	6,5	3	3		30	10	1
365.159.16.1	70 / 40	75	40	17,5	10,5	7	7	7,5	2,5	4			10	1
365.162.16.1	70 / 50	75	50	17,5	10,5	7	7	7	2,5	3,5	360	90	10	1
365.165.16.1	70 / 56	75	56	17,5	10,5	7	7	6,5	2,5	3		90	10	1
365.175.16.1	70 / 70	75	75	17,5	10,5	7	7	5,5	2,5	2,5		80	10	1
366.159.16.1	90 / 40	90	40	20	12	8	8	8,5	2,5	4,5			60	1
366.162.16.1	90 / 50	90	50	20	12	8	8	8,5	2,5	4,5			10	1
366.165.16.1	90 / 56	90	56	20	12	8	8	8	2,5	4			10	1
366.175.16.1	90 / 70	90	75	20	12	8	8	7	2,5	3			10	1
366.180.16.1	90 / 90	90	90	20	12	8	8	6,5	2,5	2,5		160	10	1
367.159.16.1	100 / 40	110	40	22,5	13,5	9	9	10	2,5	6			40	1
367.162.16.1	100 / 50	110	50	22,5	13,5	9	9	9,5	2,5	5	480	160	10	1
367.165.16.1	100 / 56	110	56	22,5	13,5	9	9	9	2,5	4,5	420	140	35	1
367.175.16.1	100 / 70	110	75	22,5	13,5	9	9	8,5	2,5	3,5		140	35	1
367.180.16.1	100 / 90	110	90	22,5	13,5	9	9	7,5	2,5	3		30	10	1
367.185.16.1	100 / 100	110	110	22,5	13,5	9	9	6,5	2	2	480	120	30	1
368.162.16.1	125 / 50	125	50	25	15	10	10	11	2,5	6			5	1
368.165.16.1	125 / 56	125	56	25	15	10	10	10,5	2,5	5,5			5	1

368.175.16.1	125 / 70	125	75	25	15	10	10	10	2,5	4,5		5	1
368.185.16.1	125 / 100	125	110	25	15	10	10	8	2	3		25	1
368.189.16.1	125 / 125	125	125	25	15	10	10	7	2	2		20	1
369.185.16.1	150 / 100	160	110	35	21	14	14	13,5	4,5	6		5	1
369.189.16.1	150 / 125	160	125	35	21	14	14	12,5	4,5	5			1
369.195.16.1	150 / 150	160	160	35	21	14	14	10,5	3,5	3		5	1
370.185.16.1	200 / 100	200	110	36	18	18	18	7	6	7			1
370.189.16.1	200 / 125	200	125	36	18	18	18	6,5	6	6,5			1
370.195.16.1	200 / 150	200	160	36	18	18	18	4,5	5	4,5			1
370.196.16.1	200 / 200	200	200	40	20	20	20	2,5	3	2,5			1
371.185.16.1	250 / 100	250	110	44	22	22	22	11	7,5	11			1
371.195.16.1	250 / 150	250	160	44	22	22	22	8,5	6,5	8,5			1
371.196.16.1	250 / 200	250	200	48	24	24	24	6,5	4	6,5			1
371.197.16.1	250 / 250	250	250	48	24	24	24	4	4	4			1
372.185.16.1	300 / 100	315	110	56	28	28	28	17	10	17			1
372.195.16.1	300 / 150	315	160	56	28	28	28	14,5	9	14,5			1
372.196.16.1	300 / 200	315	200	56	28	28	28	12	6,5	12			1
372.197.16.1	300 / 250	315	250	56	28	28	28	9,5	6,5	9,5			1
372.198.16.1	300 / 300	315	315	56	28	28	28	7	6,5	7			1