


Geberit PE Bogen



Verwendungszwecke

- Zur Gebäudeentwässerung
- Zur Grundstücksentwässerung

Eigenschaften

- Beidseitig mit Elektroschweißmuffe schweißbar

Technische Daten

Werkstoff

PE-HD

Artikel

Art.-Nr.	DN	d, ø [mm]	X [cm]	K [cm]	r [cm]	VE4 [St.]	VE3 [St.]	VE2 [St.]	VE1 [St.]
arc / Winkel: 45°									
360.045.16.1	40	40	4	2			100	10	1
361.045.16.1	50	50	4,5	2			100	10	1
363.045.16.1	56	56	4,5	2		1280	160	10	1
365.045.16.1	70	75	5	2		800	50	10	1
366.045.16.1	90	90	5,5	2		480	30	10	1
367.045.16.1	100	110	6	2,5		280	70	10	1
368.045.16.1	125	125	6,5	2,5		200	50	10	1
369.045.16.1	150	160	6,9	2			120	10	1
370.045.16.1	200	200	18	2,5	20		28	7	1
arc / Winkel: 88,5°									
361.088.16.1	50	50	6	2			50	10	1
363.088.16.1	56	56	6,5	2			260	10	1
365.088.16.1	70	75	7,5	2		480	30	10	1
366.088.16.1	90	90	8	2			80	10	1
367.088.16.1	100	110	9,5	2,5		200	50	10	1
368.088.16.1	125	125	10	2,5			160	40	1
369.088.16.1	150	160	12	2,5			72	6	1